



Technical Specifications

Technical Information

- **Dimensions:** H 170mm x W 145mm x D 200mm
- **Weight:** approx. 2.3kg, approx. 2.5kg incl. delivery accessories
- **Classification:**
 - Device (protection class according to IEC 60601) Class II
 - Application parts of Type BF
 - Degree of protection by housing IP22

Electrical Specification

- **Operating voltage:**
 - AIRcon Gen2 101200 (220V~ - 240V~)
 - AIRcon Gen2 101201 (110V~ - 120V~)
- **Mains frequency:** 50Hz / 60Hz
- **Power consumption:** max. 315VA
- **Heating plate:** 170W
- **Inspiratory tube heater:** 22V~, 30W

Operating Data

- **Warm-up time:** max. 30 min.
- **Recommended flowrate:** 2 to 80l/min
- **Humidifier system output:**
 - > 33mg/l in the range of 2 – 60l/min
 - > 10mg/l in the range of 2 – 80l/min
- **Maximum operating pressure:** 200mbar⁽¹⁾
- **Continuous noise:** < 50dB (1m)
- **Sound pressure level of the alarm:** max. 65dB
- **Max. volume of water:** 200ml

Application parts

- Heated wire breathing systems
- Temperature probe
- Heating wire adapter

WILAméd GmbH

A company of Löwenstein

Gewerbepark Barthelmesaurach
Aurachhöhe 5–7
91126 Kammerstein (Germany)



Phone: +49 9178 996999-0
Fax: +49 9178 996778
info@wilamed.com
www.wilamed.com

Humidification system

- **Gas leakage at max. operating pressure:** < 10ml/min⁽²⁾
- **Gas leakage at 60 mbar:**
 - Adults < 70ml/min⁽²⁾
 - Children < 40ml/min⁽²⁾
 - Neonates < 30ml/min⁽²⁾
- **Pressure drop:** < 0.02 (mbar*min)/l⁽²⁾
- **Internal Compliance:**
 - Adults 0.5 – 5ml/mbar⁽²⁾
 - Children 0.5 – 4ml/mbar⁽²⁾
 - Neonates 0.5 – 1.5ml/mbar⁽²⁾
- **Flow resistance:**
 - Adults < 0.06mbar/l/min at 30l/min
 - Children < 0.12mbar/l/min at 15l/min
 - Neonates < 0.74mbar/l/min at 2.5l/min

Environment

- **Temperature:**
 - when operating: +18°C to +26°C
 - during storage and transport: -25°C to +70°C
- **Gas inlet temperature:** +18°C to +26°C⁽³⁾
- **Humidity:**
 - when operating: 0 – 93% non-condensing
 - during storage and transport: 0 – 93% non-condensing
- **Atmospheric pressure:**
 - in operation 700hPa – 1060hPa
 - during storage and transport: 500hPa – 1200hPa

Measurement Range

- **Temperature sensor:**
 - 9.5°C – 50°C (patient-side)
 - 5°C – 80°C (humidification chamber)

⁽¹⁾ Unless the user instructions for the humidification chamber used prescribes lower maximum pressures
⁽²⁾ Depending on the humidification chamber used and the breathing tube system used
⁽³⁾ The maximum gas outlet temperature of the therapy device at 23°C ambient temperature is 32°C

